PRODUCT SELECTION GUIDE

The scales on this page and chart on following page are provided as general guidelines only. Each individual, based on their unique deficits, gait patterns, proprioceptive response, and lifestyle needs, will respond differently to any orthotic device. This will influence the function and compliance results.



Further information about intended use, indications and contraindications, and suggested modifications to assure optimum alignment and patient comfort can be found in the Professional Instructions packed together with each Allard AFO or can be downloaded from allardusa.com. You can also view our 8-step videos on our Allard USA YouTube channel.

ALLARD AFO PRODUCT RIGIDITY SCALE

Each Allard AFO offers different rigidity to provide the amount of support needed without over-bracing. The chart below shows the variance in the amount of support each AFO offers. For example, Ypsilon® FLOW1/2 would be considered for patients requiring minimum support while BlueROCKER® for those that require most support.



ALLARD AFO FUNCTION SCALE

As an example, Ypsilon® FLOW1/2 allows for the most ROM while BlueROCKER® offers the least. On the other hand, if you look at stability, BlueROCKER® offers the most whereas Ypsilon® FLOW1/2 provides the least.

	Ypsilon® FLOW½	ToeOFF® FLOW2½	ToeOFF® 2½ ToeOFF® 2.0 ToeOFF® KiddieGAIT®	BlueROCKER® 2½ BlueROCKER® 2.0 BlueROCKER® KiddieROCKER®
Allows Range Of Motion			••000	•0000
M-L Stability	••000			••••
A-P Stability	••000	••••	••••	00000
Dorsiflexion Assist	••000	••••	••••	••••
Spasticity Control	••000	••••	••••	00000
Proximal Control	••000	••••		00000



ALLARD AFO MUSCLE WEAKNESS GUIDES

These charts are based on R&D studies, practitioner and patient feedback.

Muscle function:

None or limited function

Full function





CUSTOM ALLARD AFOs

When patient's anatomical or function needs fall out of the parameters of the Product Rigidity or Function Scale, Allard also offers to fabricate Custom Carbon Composite AFOs. Ask Customer Service for ordering information.

